

Title **BTU Rating, Amperage, and Voltage of Castelle FaxPress and FaxPress Plus units**

Information

The value of the BTU/Hour for each model is the total heat generated by the whole unit, including the circuit board, power supply inefficiency, the fan (if there are any) and the power regulator. Please review the information below and, upon completion, if you are still in need of more information please contact Castelle Technical Support.

FaxPress/FaxPress Plus Ratings

Unit	BTU Rating (/Hr)	Wattage	Amperage	Voltage
SBE / 2500	33	9w	US: 120VAC Japan: 100VAC UK: 240VAC Int'l: 230VAC	60Hz (250mA) 50/60Hz (18VA) 50Hz 50Hz (200 mA)
5000 (4 Line)	52	40w	90-240VAC	50-60Hz
5000 (8 Line)	79	40w	90-240VAC	50-60Hz
7000	79	40w	90-240VAC	50-60Hz
7500 (DID)	147	40	90-240VAC	Hz?
Premier (Portwell)	33	300w	100-240VAC	50-60Hz
Premier (Avnet)	33	300w	100-240VAC	50-60Hz
Premier Rev 2 (Avnet) 16L	252	300w	100-240VAC	47-63Hz
Enterprise	33	300w	100-240VAC	47-63Hz
Redundant	xx	Dual 400w	90-132VAC to 180-264VAC auto select	47-63Hz

If you have any further questions and/or concerns, please contact Castelle Technical Support.

Disclaimer

The Origin of this information may be internal or external to Castelle. Castelle makes all reasonable efforts to verify this information. However, the information provided in this document is for your information only. Castelle makes no explicit or implied claims to the validity of this information. Castelle reserves the right to change, without notice, product offerings or specifications and the information in this document.

Any trademarks referenced in this document are the property of their respective owners. Consult your product manuals for complete trademark information.